

CORECLUSTER: A Degeneracy Based Graph Clustering Framework

Christos Giatsidis

Ecole Polytechnique
giatsidis@lix.polytechnique.fr

Fragkiskos D. Malliaros

Ecole Polytechnique
fmalliaros@lix.polytechnique.fr

Dimitrios M. Thilikos


CNRS, LIRMM, and UoA
sedthilk@thilikos.info

Michalis Vazirgiannis

Ecole Polytechnique and AUEB
mvazirg@lix.polytechnique.fr

Twenty-Eighth AAAI Conference on Artificial Intelligence (AAAI-14), Québec City, Canada, 2014

OVERVIEW



THE ALGORITHM

Procedure CORECLUSTER(G).

Input: A graph G .

Output: A partition of $V(G)$ into clusters.

1. $k := \delta^*(G)$.
2. $q := 0$.
3. Let $V_k, \dots, V_0$ be the core expansion sequence of G .
4. For $i = 0, \dots, k$, let G_i be the i -core of G .
5. Let $S_k = V_k$.
6. Let $\mathcal{A}_k = \{C_1^k, \dots, C_{\rho_k}^k\} = \text{Cluster}(G[S_k])$.
7. **for** $i = k - 1$ **to** 0 **do**
8. $S_i = \text{Select}(G_i, \mathcal{A}_k \cup \dots \cup \mathcal{A}_{i+1}, V_i)$,
9. let $\mathcal{A}_i = (C_1^i, \dots, C_{\rho_i}^i) = \text{Cluster}(G[S_i])$.
10. **Return** $\mathcal{A}^k \cup \dots \cup \mathcal{A}^0$.

Procedure Select($G, \mathcal{F}, V$).

Input: A candidate triple $(G, \mathcal{F}, V)$

Output: A subset S of V and a partition $\mathcal{F}'$ of $V(\mathcal{F}) \cup (V \setminus S)$.

1. **while** $\mathbf{P}^{\alpha, \beta}(v)$ is true for some $v \in V$,
2. set $\mathcal{F} \leftarrow (\mathcal{F} \setminus \{C\}) \cup \{C \cup \{v\}\}$ where
3. C is the certificate of v
4. and set $V \leftarrow V \setminus \{v\}$.
5. set $V^1 = N_G(V(\mathcal{F}))$ and $V^2 = V \setminus (V^1 \cup \mathcal{F})$.
6. **if** V^2 is either empty or an independent set of G ,
7. **then**
8. $\mathcal{F} \leftarrow \text{assign}(G, \mathcal{F}, V, V^1)$
9. $\mathcal{F} \leftarrow \text{assign}(G, \mathcal{F}, V, V^2)$
10. **return** $\emptyset$
11. **else return** $V^1 \cup V^2$.

Procedure assign($G, \mathcal{F}, V, S$).

Input: A candidate triple $(G, \mathcal{F}, V)$ and a subset S of V

Output: A partition $\mathcal{F}$

1. **while** $S \neq \emptyset$,
2. let $l = \max\{\text{span}(v) \mid v \in S\}$
3. let $L = \{v \in S \mid \text{span}(v) = l\}$
4. **for every** $v \in L$,
5. set $C' = C \cup \{v\}$ where $C = \text{argspan}(v)$
6. set $S \leftarrow S \setminus \{v\}$
7. set $\mathcal{F} \leftarrow (\mathcal{F} \setminus \{C\}) \cup \{C'\}$
8. **return** $\mathcal{F}$.

THE RESULTS

